

JOINT CUTTER

SMALL SERIES

Small joint cutters for easy tasks in road construction, gardening and landscaping - ideal for rental business

Technical data		CF-13.3 B
Max. cutting depth	mm	170
Blade-Ø	mm	300 - 450
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	13
Max. motor output	kW / PS	8,7 / 11,8
Motor output (net)	kW	8,7*
Motor type		Honda GX-390 (petrol)
Motor starter		reversing start
Cutting depth adjustment		hand wheel
Feed		manual
Contents water tank	l	23
Dimensions L/W/H (transport)	mm	820/520/870 mm (T)
Weight	kg	104

* according to operating instructions motor

Order no. 50008154

CF-13.3 B



- Optimized blade guard for maximum saw blade Ø 450 mm
- Adjustable cutting depth indicator
- Quick, easy change of cutting side

Technical data		CF-1020.1 B
Max. cutting depth	mm	200
Blade-Ø	mm	350 - 500
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	20
Max. motor output	kW / PS	8,7 / 11,8
Motor output (net)	kW	8,7*
Motor type		Honda GX-390 (petrol)
Motor starter		reversing start
Cutting depth adjustment		hand wheel
Feed		manual
Contents water tank	l	22
Dimensions L/W/H (transport)	mm	1290/570/1050 (T)
Weight	kg	121

* according to operating instructions motor

Order no. 50008501

CF-1020.1 B



- Optimized blade guard for better water flow and less adhesion of cutting slurries
- Precise cutting depth adjustment by large handwheel
- Quick, easy change of cutting side
- Water supply via water tank or external pressurised water connection possible
- High steadiness, large wheels

Technical data		CF-1020.1 D
Max. cutting depth	mm	200
Blade-Ø	mm	350 - 500
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	20
Max. motor output	kW / PS	7,3 / 9,9
Motor output (net)	kW	7,3*
Motor type diesel		Hatz 1 B40U-6
Motor starter		reversing start
Cutting depth adjustment		hand wheel
Feed		manual
Contents water tank	l	22 l
Dimensions L/W/H (transport)	mm	1260/570/1050 (T)
Weight	kg	117

* according to operating instructions motor

Order no. 50008502

CF-1020.1 D



- Optimized blade guard for better water flow and less adhesion of cutting slurries
- Precise cutting depth adjustment by large handwheel
- Quick, easy change of cutting side
- Water supply via water tank or external pressurised water connection possible
- High steadiness, large wheels