

PRODUCT INFORMATION

FLOOR SAW CF-1020.1 B



Order-no.: 50008501

The CF-1020.1 B achieves a cutting depth of 200 mm and is ideal for use in renovations and light work in landscaping or road construction. Therefore, it fits perfectly into the portfolio of construction machinery rental parks. It can convince with its very compact and transport-friendly dimensions. The extremely low installation position of the drive motor shifts the centre of gravity of the machine strongly downwards. Due to the swivel arm principle, the drive motor remains in its low installation position when the saw blade is lifted out. This achieves a particularly high level of tilt resistance and guarantees simple and easy cutting.

Application

- Powerful Honda petrol engine with cyclone air filter and low oil switch
- High tipping safety due to low centre of gravity and maximum track width
- Easy to push due to 200 mm wheels
- Vibration-damped, height-adjustable push bar
- Constant cutting shaft pressure at all cutting depths due to the swivel arm principle
- Quick and easy change of cutting side
- Optimised blade guard for better water flow and less build-up of cutting slurry
- 22-litre water tank with large filler opening
- Water tank can be swivelled to the side to fill the machine with fuel
- Crane eye



Technical data		CF-1020.1 B
Max. cutting depth	mm	200
Blade-Ø	mm	350 - 500
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	20
Max. motor output	kW / PS	8,7 / 11,8
Motor output (net)	kW	8,7*
Motor type		Honda GX-390 (petrol)
Motor starter		reversing start
Cutting depth adjustment		hand wheel
Feed		manual
Contents water tank	l	22
Dimensions L/W/H (transport)	mm	1290/570/1050 (T)
Weight	kg	121

* according to operating instructions motor

Subject to technical and optical changes and further developments.

CEDIMA Diamantwerkzeug- und Maschinenbaugesellschaft mbH

Siedemeierkamp 5 • 29227 Celle / Germany • Tel. +49 5141 8854 100 • Fax +49 5141 8854 111 • e-mail: info@cedima.com • www.cedima.com