

PRODUCT INFORMATION

FLOOR SAW CF-13.3 B



Order-no.: 50008154

The flexible floor saw can be used especially for light roadway renovations as well as for gardening and landscaping. The cutting depth is adjusted by handwheel, the excavation is realised via a low-maintenance rocker. The operator handle is rubber-mounted and therefore particularly low in vibration.

Due to its compact dimensions and easy handling, the machine is also ideal for the rental business.

Application

- Optimised blade guard for maximum cutting disc Ø 450 mm
- Reliable Honda petrol engine with cyclone air filter
- Quick and easy change of cutting side
- Infinitely variable cutting depth adjustment by means of hand crank
- Adjustable cutting depth indicator and parking brake
- Height-adjustable and low-vibration push bar
- Water supply possible via 23-litre water tank or external pressurised water connection
- Pull-out transport handle, crane eye



Technical data		CF-13.3 B
Max. cutting depth	mm	175
Blade-Ø	mm	300 - 450
Bore hole of blade	mm	25,4
Blade mounting		right or left
Max. mounting width	mm	13
Max. motor output	kW / PS	8,7 / 11,8
Motor output (net)	kW	8,7*
Motor type		Honda GX-390 (petrol)
Motor starter		reversing start
Cutting depth adjustment		hand wheel
Feed		manual
Contents water tank	l	23
Dimensions L/W/H (transport)	mm	820/520/870 mm (T)
Weight	kg	104

* according to operating instructions motor

Subject to technical and optical changes and further developments.

CEDIMA Diamantwerkzeug- und Maschinenbaugesellschaft mbH

Siedemeierkamp 5 • 29227 Celle / Germany • Tel. +49 5141 8854 100 • Fax +49 5141 8854 111 • e-mail: info@cedima.com • www.cedima.com