

FLOOR SAWS

MEDIUM SERIES

Medium-size joint cutters with latest **exhaust emission standard stage 5** suitable for cutting in narrow building sites or areas difficult to access up to heavy-duty use on building sites with high daily output

Technical data		CF-4030 D / B
Max. cutting depth	mm	210 - 410
Blade-Ø	mm	600 - 1000
Speed of cutting shaft		variabel
Bore hole of blade	mm	35 + 6-hole
Blade mounting		right or left
Max. mounting width	mm	20
Max. motor output D [B]	kW / PS	45 / 61,2 [57 / 77,5]
Motor output (net)* D / B	kW	45* / 45 (2500 min ⁻¹)
Motor type diesel		Doosan D18
Motor type petrol		Ford MSG 425
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulic
Dimensions L/W/H (transport)	mm	1625 / 1275 / 1295
Weight	kg	980

* according to operating instructions motor

Delivery inclusive:

- Blade guard 1000 mm
- Water pump
- Latest exhaust emission standard stage 5
- Telescopic visor
- Cutting shaft set for Ø 600 - 1000 mm
- Electrical cutting depth measurement
- Hydraulic steering
- Fail-safe parking brake

Accessories CF-4030 Series

Description	Order no.
Foodboard and adjustable seat	50003273
Suction plant type 5.5 for CF-4030 series	50011964
Suction blade guard for saw blade-Ø 600 mm	50011690
Green concrete conversion kit CF-4030 D/B	50010840

Order no. 50009738

CF-4030 D



Order no. on request

CF-4030 B



CF-4030 with suction plant

