

# FLOOR SAW CF-6022

Order no: 50010324

**Fully hydraulic floor saw for long and extensive cutting work in concrete or asphalt with high efficiency**



- Diesel engine with Stage V (EU) / TIER 4 (Final) Common-Rail Diesel
- Delivery incl. blade guard 1200 mm
- Fully hydraulic drive of all working functions
- Blade pick-up possible on the right or left
- Infinitely variable cutting shaft speed
- Standard auxiliary hydraulics for driving an extraction system
- Water supply through the cutting shaft

The CF-6022 is a fully hydraulic floor cutter for long and extensive cutting work in concrete or asphalt with high performance and large daily outputs. All work functions and the travel drive are carried out and controlled hydraulically.

The ergonomic driver's seat is adjustable, and the steering wheel can be mounted on the right or left, depending on the cutting side. Extensive accessory attachment kits make the CF-6022 a versatile machine for processing concrete and asphalt surfaces.

A special application is the possibility of converting the machine for microtrenching, a technology in which a slot is milled in the road or pavement to accommodate fibre optic cables.

Technical data		CF-6022
Max. cutting depth	mm	480
Blade-Ø	mm	300 - 1200
Bevel cut		stepless to 20 degrees
Speed of cutting shaft	min <sup>-1</sup>	930 - 2800
Bore hole of blade	mm	35 + 6-hole
Blade mounting		right or left
Max. mounting width	mm	13
Max. motor output	kW / PS	55,4 / 75,3
Motor output (net)*	kW	55,4* / 2800 min <sup>-1</sup>
Motor type diesel		Hatz 4H50TIC
Motor starter		electric starter
Cutting depth adjustment		electro-hydraulic
Feed		hydraulic
Dimensions L/W/H (transport)	mm	2900 / 950 / 1840
Weight	kg	ca. 1400

Subject to technical and optical changes and further developments.